



U.V. DRYING TUNNEL

- UV drying tunnel with 120W/cm lamp with a 50% or 100% power selector.
 - Cooling system by air turbines.
 - Suction of the ozone system, supretion of ozone and hot air in the working area.
 - Protection against hot and emission of UV rays of lamps.
 - Aspiration bases in all the conveyor belt punched with a good aspiration to fix the light weight supports.
 - Height regulation in/out: in order of the thickness of supports.
 - The reflector is easy to take the piees to be cleaned.
 - Parabolic UV reflector.
 - Teflon coated fiberglass conveyor belt with side reinforcements.
 - Pushing engine with a selector of speed.
 - Lamp life counter.
 - Width differents sizes usefullud.
 - 380 V / 50 Hz.
-
- BY OPTION: Quartz filter.
-
- **WORKING WIDTH: 80 cm.**
 - **WORKING WIDTH: 100 cm.**
 - **WORKING WIDTH: 120 cm.**
 - **WORKING WIDTH: 140 cm.**
 - **WORKING WIDTH: 160 cm.**
 - **WORKING WIDTH: 180 cm.**
 - **WORKING WIDTH: 200 cm.**



SPE Maquinaria para Serigrafia S.L.

Pol. Ind. "Can Humet". C/ Antoni Tàpies, 7-9 Nave E
08213 Polinyà, Barcelona (Spain)

Tel. (+34) 93 713 09 88. Fax. (+34) 93 713 06 58.

spe_sl@spesl.com www.spesl.com